


## MDD

### MANUAL TEST STAND

- 1kN capacity
- robust design
- high precision
- compact & portable
- handwheel operation
- tension & compression



Actuation testing



Spring testing



Shown with digital force gauge (not supplied)

- rugged and reliable
- holes for bench mounting
- accepts digital height scales

The MDD, combined with a Mecmesin force gauge, is ideal for low cost tensile and compression testing on the production floor or in laboratories.


Easy to use, the MDD is operated via a handwheel, which gives precise control of the crosshead, together with a lockable thumbwheel for fine adjustment.

The MDD is also fitted with a standard dovetail bracket for easy interchangeability of Mecmesin force gauges and loadcells. An optional height scale can be added for digital display of displacement and optional feet allow the MDD to be used horizontally.

versatile  
easy-to-use  
cost-effective




Tear testing





Tensile testing


## Dimensions



## Optional Extras



Extended  
Dovetail Bracket -  
raises gauge by 70mm  
(MAX LOAD 500N)



Optional Mounting Feet for  
Horizontal Operation

Mecmesin reserves the right to alter equipment specifications without prior notice.

## Specifications

### Model

### MDD - Manual Direct Drive Test Stand

Crosshead travel (both directions)

2mm per handwheel revolution

Effective crosshead travel

380mm with AFG force gauge, but without accessories and height scale (400mm with BFG)  
360mm with AFG/BFG force gauges and height scale, but without accessories

Maximum load

1000N/100kgf/220lbf

Weight

6kg

Optional Extras:

Height scale

0.01mm (0.0005in) resolution

Mounting feet

For horizontal operation

# Mecmesin

## Force and Torque Test Solutions

### Mecmesin Limited

Newton House, Spring Copse Business Park, Slinfold  
West Sussex RH13 0SZ, England

Tel +44 (0) 1403 799979 Fax +44 (0) 1403 799975

e-mail [info@mecmesin.com](mailto:info@mecmesin.com) web [www.mecmesin.com](http://www.mecmesin.com)

### Mecmesin Corporation

45921 Maries Road, Suite 120, Sterling  
Virginia 20166, U.S.A.

Tel 703-433-9247 Fax 703-444-9860

e-mail [usa-sales@mecmesin.com](mailto:usa-sales@mecmesin.com) web [www.mecmesin.com](http://www.mecmesin.com)