

# KERN HFT3T0.5

Robust industrial crane scale up to 15 t with radio display and RS-232 data interface for transferring weighing results



## Measuring system

Adjustment options:	External calibration
Linearity:	2 kg
Precision (of [Max]):	0,002
Readout [d]:	500 g
Recommended adjusting weight:	3000 kg (M3)
Reproducibility:	500 g
Resolution:	6
Stabilisation time:	2 s
Warm up time:	30 min
Weighing range [Max]:	3 t
Weighing system:	Strain gauge
Weighing units:	kg

## Display

Display digit height:	2,200 cm
-----------------------	----------

## Functions

Data hold function:	yes
Function to save totals:	yes
Peak function:	yes

## Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	0 °C
Minimum humidity:	0 %

## Power supply

Charging time:	8 h
Input voltage:	100 V - 240 V 50 / 60 Hz
Operating time (Backlight off):	80 h

## Service

DAkkS Certificate:	963-132H
ISO calibration certificate:	961-105

## Category

Category:	Balances
Product Group:	Crane scale

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	525 x 350 x 300 mm
Gross weight:	30 kg
Net weight:	28 kg
Shipping method:	Parcel service

# KERN HFT3T0.5



Robust industrial crane scale up to 15 t with radio display and RS-232 data interface for transferring weighing results

## Construction

Overall dimensions mounted (WxDxH):	130 x 650 x 130 mm
-------------------------------------	--------------------