

# C.A 745N

## Digital voltage tester with LCD screen



## **Essential!**

- Automatic recognition of AC and DC voltage
- No risk of tripping the high-sensitivity RCDs when testing phase/earth
- Phase test with a single test probe
- Resistance and continuity testing
- Removable test probes



















## Safe and simple to use

Electricians, heating engineers, mechanics, maintenance technicians..., **the C.A 745N tester** is designed specially for you. The C.A 745N is a simple, effective instrument equipped with automatic DC/AC recognition. The test probes are easy to remove and replace. They are stowed in a compartment built into the instrument.

To protect users, the C.A 745N offers a high level of safety.

TECHNICAL SPECIFICATIONS	C.A 745N
Voltage test	12 V to 690 V AC/DC (7 segments)
Impedance	400 kΩ
Phase/neutral identification	Flashing "Ph" diode and intermittent beep for U > 100 Vac
Operating frequency	DC and 50/60 Hz
Polarity test	"+" and "-" symbols
Voltage protection	Up to 1,100 V
Audible continuity test	$R < 2 \text{ k}\Omega$
Resistance test	2 k $\Omega$ to 300 k $\Omega$ (3 segments)
Safety for resistance	Audible and visual indication if a voltage is present (>12 Vdc, 50 Vac)

#### **GENERAL SPECIFICATION**

Power supply	2 x 1.5 V batteries (LR03 or AAA)
Battery life	150 hours with alkaline batteries
Climatic conditions	Temperature: -10 °C to +55 °C / Relative humidity: 10 to 80 % RH
Dimensions / weight	180 x 52 x 45 mm / approx. 200 g
Ingress protection	IP54
Use	600 V CAT III installations as per IEC 61010-1, IEC 61010-031, IEC 61010-2-033

#### References to order

C.A 745N ..... P01191743Z

#### STATE AT DELIVERY

C.A 745N delivered in blister pack with:

- 1 set of RD/BK extra-fine CAT III/CAT IV test probes
- 2 x 1.5 V AAA / LR3 alkaline batteries
- 1 user manual in 5 languages



#### **ACCESSORIES & REPLACEMENT PARTS**

Set of red/black CAT III/IV test probes	. P01102152Z
Set of red/black test probes - Ø 2 mm, CAT II	. P01102153Z
Set of red/black test probes - Ø 4 mm, CAT II	. P01102154Z
C.A 753 adapter for 2P+E sockets	. P01191748Z
Velcro strap x 5	. P01102113
1.5 V LR3 / AAA alkaline battery (x 1)	. P01296032
Bag compatible with MultiFix accessory, 120 x 200 x 60	. P01298074
MultiFix mounting accessory	. P01102100Z

MultiFix mounting





 Bag compatible with MultiFix accessory



#### FRANCE Chauvin Arnoux

190, rue Championnet 75876 PARIS Cedex 18 Tel: +33 1 44 85 44 38 Fax: +33 1 46 27 95 59 export@chauvin-arnoux.fr www.chauvin-arnoux.com

#### UNITED KINGDOM Chauvin Arnoux LTD

Unit 1 Nelson Ct, Flagship Sq, Shaw Cross Business Pk Dewsbury, West Yorkshire - WF12 7TH Tel: +44 1924 460 494 Fax: +44 1924 455 328 info@chauvin-arnoux.co.uk www.chauvin-arnoux.com

### MIDDLE EAST Chauvin Arnoux Middle East

P.O. BOX 60-154 1241 2020 JAL EL DIB - LEBANON Tel: +961 1 890 425 Fax: +961 1 890 424 camie@chauvin-arnoux.com www.chauvin-arnoux.com For assistance and ordering